



WIRE ROPES ÇELİK HALATLAR

6x19S + FC




Nominal Rope Diameter (mm)	Unit Weight (Kg/Mt)	Minimum Breaking Load 1570 N/mm ² (kN)	Minimum Breaking Load 1770 N/mm ² (kN)	Cross Section Area (mm ²)
6	0,128	18,7	21,0	14,1
6,5	0,150	21,9	24,7	16,6
7	0,174	25,4	28,6	19,2
8	0,228	33,2	37,4	25,1

6x19S + IWRC (SWR K-200 S)



Nominal Rope Diameter (mm)	Unit Weight (Kg/Mt)	Minimum Breaking Load 1570 N/mm ² (kN)	Minimum Breaking Load 1770 N/mm ² (kN)	Cross Section Area (mm ²)
6	0,146	20,2	22,6	15,4
6,5	0,171	23,4	26,5	18,6
8	0,259	35,9	40,2	28,2


SWR 8x19S + FC



Nominal Rope Diameter (mm)	Unit Weight (Kg/Mt)	Minimum Breaking Load 1370/1770 N/mm ² (kN)	Minimum Breaking Load 1570 N/mm ² (kN)	Cross Section Area (mm ²)
8	0,218	28,1	29,4	22,3
9	0,275	35,6	37,3	28,3
10	0,340	44,0	46,0	34,9
11	0,411	53,2	55,7	42,2
12	0,490	63,3	66,2	50,3
13	0,575	74,3	77,4	59,0
14	0,666	86,1	90,2	68,4
16	0,870	113,0	118,0	89,3


WIRE ROPES ÇELİK HALATLAR

SWR K-240 W




Nominal Rope Diameter (mm)	Unit Weight (Kg/Mt)	Minimum Breaking Load 1570 N/mm ² (kN)	Cross Section Area (mm ²)
8	0,268	43,3	30,4
10	0,423	67,7	49,4
11	0,512	81,9	59,7
12	0,610	97,4	71,1
13	0,715	114,0	83,4
14	0,829	133,0	96,7
16	1,083	173,0	126,0

SWR K-240 W



Nominal Rope Diameter (mm)	Unit Weight (Kg/Mt)	Minimum Breaking Load 1770 N/mm ² (kN)	Cross Section Area (mm ²)
6,5	0,177	31,5	20,1

SWR K-200 S



Nominal Rope Diameter (mm)	Unit Weight (Kg/Mt)	Minimum Breaking Load 1570 N/mm ² (kN)	Cross Section Area (mm ²)
8	0,243	38,5	27,4
10	0,379	58,9	42,8
11	0,456	73,2	51,7
12	0,544	84,9	61,6
13	0,645	101,9	72,3
14	0,745	118,2	83,9
16	0,971	150,0	109,5